Rockford Sanitary Systems, Inc.
ROCKFORD, IL 61125-0963
(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108
WEB SITE-www.rkfdseparators.com E MAIL-rssem@inwave.com

MODEL NO. G-1012-L GREASE SEPARATOR

DRAWN BY QUOTE # JOB NAME W.R.W. DUTLET OPTIONAL FEATURES (ADDITIONAL COST) □ EPOXY COATING STAINLESS STEEL CONSTRUCTION □ SEDIMENT BASKET □ FILTER MEDIA DRAW DFF VALVE □ ALTERNATE INLET & DUTLET SIZE ____ INCHES INLET - 14,25 10.75 -- 8.75 -4.37 5.37 11.37 9.63 7.63 **INLET** DUTLET

Specifications

Rockford Model G-1012-L all welded 10 Ga. steel separator for on the floor (or partially recessed) installation, 8 g.p.m. intermittent flow, 1.50" tapped inlet and outlet connection, 12 lbs. greasy sludge capacity, visible double-wall outside trap seal, easily removable filter screen and separator screen, gasketed cover hand tightened to body with safety catch bolt assemblies, enamel coated inside & outside.

Optional features (Additional cost) listed above

Approved By	Company	Date