Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108 WEB SITE-www.rkfdseparators.com E MAIL-rssem@inwave.com

MODEL NO. G-25-LO-RGREASE SEPARATOR

DRAWN BY	QUOTE #	JOB NAME	
W.R.W.	T T T T T T T T T T T T T T T T T T T	SSD WWL	
4V 11 \1 VV 1			
ı	<u>U</u>	OPTIONAL FEATURES (ADDITIONAL COST)	
		EPEXY COATING	
		☐ STAINLESS STEEL CONSTRUCTION ☐ SEDIMENT BASKET ☐ FILTER MEDIA	
	F	☐ DRAW OFF VALVE ☐ ALTERNATE INLET & OUTLET SIZE INCHES	
_			
INLET			
4			
_	_		
	Г		
L			
		26,63 —	
	DUTLET		
-	26,75	20.75	
-	→ 17.25 →	10.38	
(™ O <mark></mark>			
l		13.50	
	10	.25	
6,50			
		†	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
Ţ			
INLET		JTLET	
Specifications			

Sherii ira aniis

Rockford Model G-25-LO-R all welded 10 Ga. steel separator for on the floor (or partially recessed) installation, 20 g.p.m. intermittent flow, 2.00" tapped inlet and outlet connection, 80 lbs. greasy sludge capacity, visible double-wall outside trap seal, easily removable filter screen and separator screen, gasketed cover hand tightened to body with safety catch bolt assemblies, enamel coated inside & outside.

Optional features (Additional cost) listed above

Approved By	Company	Date