Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108 WEB SITE-www.rkfdseparators.com E MAIL-rssem@inwave.com

MODEL NO. G-30-L0-MGREASE SEPARATOR

DRAWN BY JOB NAME QUOTE # W.R.W. OPTIONAL FEATURES (ADDITIONAL COST) □ EPOXY COATING ☐ STAINLESS STEEL CONSTRUCTION □ SEDIMENT BASKET □ FILTER MEDIA ☐ DRAW OFF VALVE ☐ ALTERNATE INLET & OUTLET SIZE ____ INCHES DUTLET INLET 38,43 -20.75 30.75 10.38 13,50 10.25 6.50 DUTLET **INLET**

Specifications

Rockford Model G-30-LO-M all welded 10 Ga. steel separator, 23 gallon static capacity, 30 g.p.m. intermittent flow, 3.00" tapped inlet and outlet connection, 90 lbs. greasy sludge capacity, visible double-wall outside trap seal, easily removable filter screen gasketed cover hand-tightened to body with safety-catch bolt assemblies, enamel coated inside and outside.

Optional features (Additional cost) listed above

Approved By Company Date