



Rockford Sanitary Systems, Inc.

ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108

WEB SITE-www.rkfdseparators.com E MAIL-rssem@inwave.com

MODEL NO. G-3628-L

GREASE SEPARATOR

DRAWN BY

W.R.W.

QUOTE #

JOB NAME

OUTLET

OPTIONAL FEATURES (ADDITIONAL COST)

- ☐ EPOXY COATING
☐ STAINLESS STEEL CONSTRUCTION
☐ SEDIMENT BASKET ☐ FILTER MEDIA
☐ DRAW OFF VALVE
☐ ALTERNATE INLET & OUTLET SIZE ____ INCHES

INLET

15.00

36.00

18.00

30.00

22.00

INLET

41.13

30.38

26.25

OUTLET

Specifications

Rockford Model G-3628-L all welded 10 Ga. steel separator for on the floor (or partially recessed) installation, 100 g.p.m. intermittent flow, 4.00" tapped inlet and outlet connection, 350 lbs. greasy sludge capacity, visible double-wall outside trap seal, easily removable filter screen and separator screen, gasketed cover hand tightened to body with safety catch bolt assemblies, enamel coated inside & outside.

Optional features (Additional cost) listed above

Approved By

Company

Date